

Mesh per Linear Inch	Diameter of Wire (Dec. of In.)	Width of Opening		Open Area
		Inch	Millimeter	
2	0.054	0.446	11.33	79.60%
3	0.041	0.292	7.42	76.70%
4	0.035	0.215	5.46	74.00%
5	0.032	0.168	4.27	70.60%
6	0.028	0.139	3.53	69.60%
7	0.028	0.115	2.92	64.80%
8	0.025	0.1	2.54	64.00%
9	0.023	0.088	2.24	62.70%
10	0.02	0.08	2.03	64.00%
12	0.018	0.065	1.65	60.80%
14	0.017	0.054	1.37	57.20%
16	0.016	0.0465	1.18	55.40%
18	0.015	0.0406	1.03	53.40%
20	0.014	0.036	0.91	51.80%
22	0.0135	0.032	0.81	49.60%
24	0.013	0.0287	0.73	47.40%
26	0.011	0.0275	0.7	51.10%
28	0.01	0.0257	0.65	51.80%
30	0.0095	0.0238	0.61	51.00%
32	0.009	0.0223	0.57	50.90%
34	0.009	0.0204	0.52	48.10%
36	0.009	0.0188	0.48	45.80%
38	0.0085	0.0178	0.45	45.80%
40	0.0085	0.0165	0.42	43.60%
45	0.008	0.0142	0.36	40.80%
50	0.0075	0.0125	0.32	39.10%
55	0.007	0.0112	0.28	37.90%
60	0.0065	0.0102	0.26	37.50%